



# Westbuild PRO™

## General Purpose Primer

**A multi-use primer, suited to Westbuild Wet Area Waterproofing and levelling products.**

Westbuild PRO™ General Purpose Primer is a multipurpose SBR polymer system designed to be used with Wet Area Waterproofing and Westbuild levelling compounds.

Westbuild PRO™ General Purpose Primer is developed to improve system strength and application adhesion, reduce the formation of surface bubbling and promote maximum adhesion and coverage of the overlaying product.

Westbuild PRO™ General Purpose Primer is low V.O.C.

### Advantages

- Adhesion promoter for hard to bond substrates.
- Rapid drying for a faster overcoat.
- Improves application workability of the overcoat.
- Prevents air bubbles rising from the sub floor.
- Consolidates dusty or powdery surfaces prior to over coating.
- Low V.O.C.
- Environmentally Safe and solvent free.



### Product Attributes

<u>Uses</u>	Adhesion promoter for hard to bond substrates. Designed for use with Westbuild PRO™ Wet Area Waterproofing and Westbuild levelling compounds.
<u>Substrates</u>	Concrete, render and masonry. Plaster board, fibre cement and structural sheeting. Aerated concrete panels and blocks. The substrate must be porous and free from release agents. For more information on suitable substrates or substrates that are not listed above, please contact a Westbuild representative.
<u>Performance</u>	Civil, commercial and industrial.
<u>Colour</u>	Orange
<u>Packaging</u>	12kg Pail. 32 Pails per Pallet (384kg).
<u>Coverage</u>	Depending on porosity and overall condition of the substrate. As a general guide, allow 1 litre per 7-10m <sup>2</sup> based on 1 coat. Always ensure you have adequate material to complete the works.
<u>Shelf Life &amp; Storage</u>	Store unopened product in a cool, dry place away from direct sunlight.



**Technical Data**

**Product Identity**      *Form*      Liquid  
                                 *Colour*      Orange

**Typical Performance**

Curing Time	2 hours
Colour	Orange Liquid
Recoat (25°C)	1 hour
Wet Film	100-140 microns
Clean up	Water
Shelf life	12 Months
DG Class	N/A
Flash Point	N/A
V.O.C.	0%

**Installation**

**Suitability Assessment**      It is recommended before commencing the application, applicators should determine the suitability of a product for the intended use, over a typical area to ensure satisfactory adhesion. It is the responsibility of the applicator to perform this assessment and accept the substrate suitability before any application starts. Details contained in the data sheet are general. For any situation or items not covered in this data sheet, it is the responsibility of the applicator to contact Westbuild for further advice.

**Surface Preparation**      Surface preparation is vital for optimum adhesion and results. Ensure all substrates are structurally sound, free from loose contaminating material and completely dry.

**Application temperature should be between the range of 7°C - 35°C.**

Stir contents well before use. Do not dilute as Westbuild PRO™ General Purpose Primer is ready to use. The product may be applied by brush, roller (universal, medium nap cover) or spray unit.

**Coverage**      Depending on porosity and overall condition of the substrate. As a general guide, allow 1 litre per 7-10m<sup>2</sup> based on 1 coat. Always ensure you have adequate material to complete the works.

**Cleaning**      Clean up with water only while the material is still wet.

**Attention**      **Do NOT apply when surface temperature is below 7°C or above 35°C.**



### **Safety Precautions**

Westbuild PRO™ General Purpose Primer SDS is available from our website ([www.westbuildgroup.com](http://www.westbuildgroup.com)) or Westbuild upon request.

Ensure good ventilation and avoid inhaling vapours. Avoid skin and eye contact. Wear gloves and eye protection. Remove splashes on skin immediately and remove contaminated clothing.

Keep out of reach of children.

Keep container sealed when not in use.

Do not swallow.

### **First Aid**

If poisoning occurs, contact a doctor or poisons information centre: Ph. 13 11 26.

If swallowed, do not induce vomiting. Give a glass of water to drink.

If in eyes, hold eyes open and flood with water for at least 15 minutes.

If not breathing, apply artificial respiration.

### **Technical/Safety Data**

TECHNICAL DATA SHEETS (TDS) AND SAFETY DATA SHEETS (SDS) are available on request and should always be referenced before handling this product and before the commencement of any works. A WESTBUILD Representative is always available should you require further information. Visit our website for further information on the use of this product and suitability for your application.

### **Warranty**

All Westbuild products are designed for use together as a complete system providing a guarantee our products will perform harmoniously and to specification.

Our warranties demonstrate our ongoing commitment to the performance of our products and a promise of exceptional quality control.

### **Related Products**

Westbuild PRO™ Wet Area Waterproofing

Westbuild Easy Screed™

Westbuild Level It™

Any advice, recommendation, information, assistance or service provided by Westbuild® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

It is the responsibility of the user to ensure that products are used in accordance with the Westbuild Products Pty Ltd instructions for use, and Australian Standard procedures in applications for which they are intended. Westbuild Products Pty Ltd and its associated companies cannot guarantee and are not liable for the use of their products outside of Australian Standards guidelines and the Westbuild Products Pty Ltd instructions for use. The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge at time of printing. Freedom from patent restrictions should not be assumed.

Westbuild® reserves the right to update information without prior notice, to reflect ongoing research and product development.

WESTBUILD CONTACT DETAILS  
PHONE: 08 9309 2029  
FAX: 08 9302 1129  
Email: [technical@westbuildgroup.com](mailto:technical@westbuildgroup.com)