



PAVE N' LOCK™

A blend of selected sands and gelling agents. This material is best suited for filling joints (2-4mm) between paving blocks and bricks.

PAVE N' LOCK™ is formulated to allow rapid filling of paving joints and will cure through drying to lock in paving joints.

Advantages

Minimise windblown joint erosion
Helps retain stability of the joint
Easy to apply and formulated to allow rapid filling of paving joints

**** New low-dust formulation**

**** Rainproof packaging**



Product Attributes

Uses

Recommended For Driveways & Footpaths
Commercial and public recreation areas
Where there is traffic movement
Where mobile vacuum sweepers are used
Can be used in high wind areas

For more information on suitable substrates or substrates that are not listed above, please contact a Westbuild representative.

Performance Residential, commercial and medium industrial.

Packaging 20kg Rainproof bag (50 bags per tonne). 60 bags per pallet (1.12 tonne).

Coverage 20kg of PAVE N' LOCK will cover approximately 4-6m² of paving. The paving joint widths and paver thickness will ultimately determine the coverage of PAVE N' LOCK.

Shelf Life & Storage 12 months when stored in a dry place in the original, unopened packaging. Do not store on concrete floors. High levels of humidity will reduce the shelf life of the product.



Installation

Surface Preparation

Ensure the pavers are completely dry before the installation of PAVE N' LOCK.

Application

Spread PAVE N' LOCK™ evenly over dry pavers and sweep into the joints.

If suitable for your pavers, vibrate the entire area using a vibrating plate compactor.

Sweep away all excess PAVE N' LOCK™ sand and remove it from the paved area to minimise risk of discolouration. (NOTE: PAVE N' LOCK™ left on the paved surface could cause discolouration if wet).

With a fine mist spray, spray the area thoroughly.

Repeat this 3-4 times, until the water has soaked through the entire depth of the PAVE N' LOCK™. Do not flood the area or spray the PAVE N' LOCK™ out of the joints.

Allow PAVE N' LOCK™ to cure through drying.

Setting Time

PAVE N' LOCK activates with a repeated fine mist spray, ensuring water penetrates through the joint. It will begin to gel once it has been wet, but will need to fully dry out to gain strength and become bonded. Drainage and permeability of the base, and weather conditions will both determine the rate at which PAVE N' LOCK will dry.

Attention

Ensure the paving is completely dry with no signs of dampness before you sweep in the PAVE N' LOCK™. Damp or wet pavers can cause the PAVE N' LOCK™ to gel and cure too early, before it is swept into the paving joints.

Ensure the surface is completely clean and all PAVE N' LOCK residue is removed before mist spraying the surface. If there is residue on the surface, it may stain the pavers.

Do not use PAVE N' LOCK™ on steep inclines.

PAVE N' LOCK™ is not recommended when water is likely to run over the joints on a continuous basis.

Do not use around swimming pool pavers or headers.

Not to be used in structural or building applications.

PAVE N' LOCK™ gels and forms a durable surface. Over time, factors including heavy or continuous water runoff, other environmental elements and general wear may result in a need for maintenance on the paving joints in some areas.

Warranty is limited to the value of the bag.

Risk

PAVE N' LOCK™ contains fine sand. A dust mask should be worn when handling the material. Contact with the eyes and repeated and prolonged skin contact should be avoided.



Safety Precautions

Avoid contact with the eyes and skin with proper use of suitable protective clothing with both wet and dry cement based products. Always wear a P1, P2 or suitable dust mask when exposed to product containing dust.

Technical/Safety Data

TECHNICAL DATA SHEETS (TDS) AND SAFETY DATA SHEETS (SDS) are available on request and should always be referenced before handling this product and before the commencement of any works. A WESTBUILD Representative is always available should you require further information. Visit our website for further information on the use of this product and suitability for your application.

Related Products

WESTBUILD Sand & Cement
WESTBUILD Mortar General Purpose Grey / Cream 20kg

WESTBUILD has no control over the use of this product. Recommendations and advice on the use of this product should be taken as a guide only. By the use of this product, you agree that Westbuild Products Pty Ltd, or any affiliated companies shall not be liable for any loss, damage, injury or death resulting from the use of this product. To the full extent permitted by law, Westbuild Products Pty Ltd liability is limited to their discretion to the replacement or re-supply of similar goods. Warranty is limited to the value of the bag.

It is the responsibility of the user to ensure that products are used in accordance with the Westbuild Products Pty Ltd instructions for use, and Australian Standard procedures in applications for which they are intended. Westbuild Products Pty Ltd and its associated companies cannot guarantee and are not liable for the use of their products outside of Australian Standards guidelines and the Westbuild Products Pty Ltd instructions for use. The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge at time of printing. Freedom from patent restrictions should not be assumed.

Pave N' Lock is a trademark to Westbuild Products Pty Ltd.

WESTBUILD CONTACT DETAILS
PHONE: 08 9309 2029
FAX: 08 9302 1129
Email: technical@westbuildgroup.com