

# Dried Sand

## Kiln-Dried White Sand

Westbuild Dried Sand is a conveniently packaged white, washed and dried, West Australian Sand with a diverse range of uses around the building site, home and garden.

Dried Sand is an ideal infill for artificial turf and paving. It can also be used for general landscaping and in preparation with other building materials to prepare white mortars or jointing cement.

### Advantages

- Kiln dried – no moisture content
- Quick and easy to use – can be brushed directly from the bag
- Convenient 20kg size for home or work site
- Can be stored for long periods of time
- Premium Quality
- Western Australian sand

**\*\*20kg Now available in new Rainproof Packaging**



### Product Attributes

#### Uses

**Infill for artificial turf:** helps to weigh down synthetic grass, providing stability and eliminating wrinkles and folds. The sand surrounds each blade of grass ensuring the blades stand tall for an aesthetically pleasing finish.

**Paving gap & joint-fill sand:** Prevents unwanted movement when brushed between block paving joints and flows easily into gaps. Simply sweep into joints and paving gaps to provide extra rigidity and strength.

**White mortar/jointing cement:** suitable for mixing with white cement to form a white brick/block mortar.

**General use:** ideal for general handyman and landscaping use, including repair work and as a filling sand.

For more information on suitable substrates or substrates that are not listed above, please contact a Westbuild representative.

#### Colour

White

#### Performance

Residential, commercial and industrial.

#### Packaging

20kg Rainproof bag (50 bags per tonne.) 60 bags per pallet (1200kg).



<u>Coverage/Yield</u>	Artificial Turf – as turf infill, 1x 20kg Bag covers approximately 2m <sup>2</sup> of turf. Paving – as a gap-filler, 1x 20kg Bag covers approximately 5m <sup>2</sup> of paving. General – 1x 20kg Bag covers approximately 1m <sup>2</sup> at a thickness of 10mm.
<u>Shelf Life &amp; Storage</u>	Westbuild Dried Sand, in 20kg Rainproof Bags can be stored outside in any weather conditions and can be stored for extended periods of time.

---

<u>Attention</u>	<b>Sand is a natural product and is sourced from a variety of locations. Slight variation in both colour and clay content may occur from source to source.</b> <b>Due to expected natural colour variation in sand, always check sand colour is appropriate before using in colour-based renders and before matching to existing brickwork.</b> <b>Application of dried sand as infill during wet or damp conditions is not recommended.</b>
------------------	--

---

<u>Risk</u>	Although this product is not considered hazardous, a dust mask and safety glasses should be worn when handling the material. Contact with the eyes and repeated and prolonged skin contact should be avoided.
-------------	---

---

<u>Safety Precautions</u>	Avoid contact with the eyes and skin with proper use of suitable protective clothing, including safety glasses. Always wear a P1 or P2 dust mask suitable for particulates when exposed to dust.
---------------------------	--

---

<u>Technical/Safety Data</u>	TECHNICAL DATA SHEETS (TDS) AND SAFETY DATA SHEETS (SDS) are available on request and should always be referenced before handling this product and before the commencement of any works. A WESTBUILD Representative is always available should you require further information. Visit our website for further information on the use of this product and suitability for your application.
------------------------------	--

---

<u>Related Products</u>	Westbuild Easy Screed Westbuild Sand and Cement Westbuild White Washed Sand Westbuild Brickies Sand Westbuild Plastering Sand
-------------------------	---

It is the responsibility of the user to ensure that products are used in accordance with the Westbuild Products Pty Ltd instructions for use, and Australian Standard procedures in applications for which they are intended. Westbuild Products Pty Ltd and its associated companies cannot guarantee and are not liable for the use of their products outside of Australian Standards guidelines and the Westbuild Products Pty Ltd instructions for use. The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge at time of printing. Freedom from patent restrictions should not be assumed.

WESTBUILD CONTACT DETAILS  
PHONE: 08 9309 2029  
FAX: 08 9302 1129  
Email: [technical@westbuildgroup.com](mailto:technical@westbuildgroup.com)