

Plastering Sand

General Purpose Screened Sand

Westbuild Plastering Sand is a conveniently packaged, screened West Australian Sand.

Plastering Sand is used for general plastering and rendering around the building site, home and garden.

Advantages

- Convenient Handy Pak size for home or work site
- Quick and easy to use
- Can be stored for long periods of time
- Premium Quality
- Australian Sourced



Product Attributes

<u>Uses</u>	Ideal for mixing with cement and lime to form a render that is easy to apply and finish. Best for rendering brick or block work. General plastering. Topping mixes. For more information on suitable substrates or substrates that are not listed above, please contact a Westbuild representative.
<u>Colour</u>	Yellow/orange, natural sand
<u>Packaging</u>	20kg Polyethylene Bag – 64 bags / pallet (1.28 tonne)
<u>Coverage</u>	To cover 0.25m ³ you will require approximately 18 bags of plastering sand. To cover 0.5m ³ you will require approximately 36 bags of plastering sand.
<u>Shelf Life & Storage</u>	Supplied in a UV stabilised polyethylene bag and designed to be stored indoors or outdoors.



Attention

Sand is a natural product and is sourced from a variety of locations. Slight variation in both colour and clay content may occur from source to source.

Due to expected natural colour variation in sand, always check sand colour is appropriate before using in colour-based renders and before matching to existing brickwork.

Risk

Although this product is not considered hazardous, a dust mask and safety glasses should be worn when handling the material. Contact with the eyes and repeated and prolonged skin contact should be avoided.

Safety Precautions

Avoid contact with the eyes and skin with proper use of suitable protective clothing, including safety glasses. Always wear a P1 or P2 dust mask suitable for particulates when exposed to dust.

Technical/Safety Data

TECHNICAL DATA SHEETS (TDS) AND SAFETY DATA SHEETS (SDS) are available on request and should always be referenced before handling this product and before the commencement of any works. A WESTBUILD Representative is always available should you require further information. Visit our website for further information on the use of this product and suitability for your application.

Related Products

General Purpose Grey Cement

It is the responsibility of the user to ensure that products are used in accordance with the Westbuild Products Pty Ltd instructions for use, and Australian Standard procedures in applications for which they are intended. Westbuild Products Pty Ltd and its associated companies cannot guarantee and are not liable for the use of their products outside of Australian Standards guidelines and the Westbuild Products Pty Ltd instructions for use. The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge at time of printing. Freedom from patent restrictions should not be assumed.

WESTBUILD CONTACT DETAILS
PHONE: 08 9309 2029
FAX: 08 9302 1129
Email: technical@westbuildgroup.com